

U.S. DEPARTMENT OF LABOR
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
<b>MATERIAL SAFETY DATA SHEET</b>
REQUIRED UNDER USDL SAFETY AND HEALTH REGULATION FOR SHIP REPAIRING, SHIPBUILDING, AND SHIPBREAKING (29 CFR 1915, 1916, 1917)

Identity (As used on label and list): **Colored PTFE Thread Seal Tape**

*Section I*

<b>Manufacturer's Name:</b> Ratermann Manufacturing,	<b>Emergency Telephone Number</b> 800-537-7139
<b>Address : 601 Pinnacle Place</b> Livermore, CA 94550	<b>Telephone Number for Information</b> 925-606-2949
	<b>Date Prepared:</b> 4/26/2005
	<b>Signature of Preparer (Optional)</b>

*Section II- Hazardous Ingredients/ Identity Information*

**Hazardous Components** (Specific Chemical Identity: Common Name(s)) OSHA PEL ACGIH TLV  
Other Limits

Chemical Name	%	CAS No.
Polytetrafluoroethylene	98	900-2-84-0
Various Inorganic Pigments	2	
PTFE Tape, as such is not a hazardous material. It is processed solid polymer, temperature range -450F to +500F		

*Section III- Physical / Chemical Characteristics*

<b>Boiling Point</b>	N/A	<b>Specific Gravity (H<sub>2</sub>O=1)</b>	2.1 to 2.2
<b>Vapor Pressure (mm Hg)</b>	N/A	<b>Melting Point</b>	341C (642F)
<b>Vapor Density (Air=1)</b>	N/A	<b>Reactivity in Water</b>	None
<b>Solubility in Water</b>	Insolube	<b>Appearance and Odor</b>	White or colored

*Section IV- Fire and Explosion Hazard Data*

<b>Flash Point</b> (Method Used): N/A	<b>Flammable Limits:</b> N/A	LEL	UEL
---------------------------------------	------------------------------	-----	-----

**Extinguishing Media:** N/A Use media suitability for surrounding fire

**Special Fire Fighting Procedures:**

Self contained breathing apparatus with full facepiece & protective clothing if involved with other materials

**Unusual Fire and Explosion Hazards:** Product will emit toxic fumes at high temperatures

Above 800F: Tetrafluoroethylene; Above 825F: Hexafluoroethylene; Above 885F: Perfluoroisbutylene; Above 930F: Carbonyl Fluoride

---

**Section V - Reactivity Data**

---

<b>Stability</b>	Unstable	<b>Conditions to Avoid</b> Heating above 750F for prolonged periods of time
	Stable	

**Incompatibility** (Materials to Avoid): Molten Alkali Metals: Interhalogen Compounds

---

**Hazardous Decomposition of By-Products** :See section 4

---

<b>Hazardous</b>	May Occur	<b>Conditions to Avoid:</b> N/A
<b>Polymerization</b>	Will Not Occur	

---

**Section VI - Health Hazard Data**

---

**Route(s) of Entry:**

---

Inhalation: No toxic effect from dust

---

Eyes: Mechanical irritation

---

Skin: Non-irritating and Non-absorbing

---

Ingestion: PTFE has shown to be inert when ingested by rats

---

**Acute:** Flu like transient sickness

---

**Chronic:** Could be fatal

---

**Signs and symptoms of Exposure:** Flu like fever

---

**Medical conditions generally aggravated by exposure:** Respiratory inflammation

---

**Emergency and first aid procedures:** Move to fresh air, refer to physician

---

---

**Section VII- Precautions for Safe Handling and Use**

---

**Steps to Be Taken in Case Material is Released or Spilled**

Sweep up to prevent slippage on tape

---

**Waste Disposal Method**

Confirming to all application regulations

---

**Precautions to Be Taken in Handling and Storing**

No unusual precautions

---

**Other Precautions**

None

---

---

**Section VIII- Control Measures**

---

**Respiratory Protection** (Specify Type): Not Needed

---

Ventilation	<b>Local Exhaust:</b> not needed	<b>Special:</b> N/A
	<b>Mechanical (General):</b> not needed	<b>Other:</b> not needed

**Protective Gloves:** Not needed

**Eye Protection:** not needed

---

**Other Protective Clothing or Equipment:** Not needed

---

**Work/Hygenic Practices:** No smoking while handling material

---